

SAFETY DATA SHEET

Refresh

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Refresh

Product no.

AG-199

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning product

Uses advised against

Cleaning product

1.3. Details of the supplier of the safety data sheet

Company and address

Tetrachem Limited

Unit 1C Arrow Court industrial estate, Kington

HR53ER Herefordshire

United Kingdom

07401615059

01544 231159

Contact person

Joe Pritchard

E-mail

joe@auto-glanz.co.uk

Revision

12/08/2024

SDS Version

1.0

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements



Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour. (H225)

Causes serious eye irritation. (H319)

May cause drowsiness or dizziness. (H336)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention

Wash hands thoroughly after handling. (P264)

Wear eye protection/protective gloves/protective clothing. (P280)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

ethanol;ethyl alcohol

1-methoxy-2-propanol;monopropylene glycol methyl ether

Additional labelling

Not applicable.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

| Product/substance | Identifiers | % w/w | Classification | Note |
|---|--|--------|---|------|
| ethanol;ethyl alcohol | CAS No.: 64-17-5 EC No.: 200-578-6 UK-REACH: Index No.: 603-002-00-5 | 60-80% | Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %) | |
| 1-methoxy-2- propanol;monopropylene glycol methyl ether | CAS No.: 107-98-2 EC No.: 203-539-1 UK-REACH: Index No.: 603-064-00-3 | 15-25% | Flam. Liq. 3, H226 STOT SE 3, H336 | [1] |



ethyl acetate CAS No.: 141-78-6 5-10% EUH066 [1]

EC No.: 205-500-4 Flam. Liq. 2, H225 UK-REACH: Eye Irrit. 2, H319 Index No.: 607-022-00-5 STOT SE 3, H336

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure. Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Refresh www.almego.com



Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: ●3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Store in a cool, well ventilated area. Keep container tightly closed.

Protect from sunlight.

Incompatible materials

Refresh www.almego.com



Strong acids Strong oxidizing agents

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol;ethyl alcohol

Long term exposure limit (8 hours) (ppm): 1000 Long term exposure limit (8 hours) (mg/m³): 1920

1-methoxy-2-propanol;monopropylene glycol methyl ether

Long term exposure limit (8 hours) (ppm): 100 Long term exposure limit (8 hours) (mg/m³): 375

Short term exposure limit (15 minutes) (ppm): 150

Short term exposure limit (15 minutes) (mg/m³): 560

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

ethyl acetate

Long term exposure limit (8 hours) (ppm): 200 Short term exposure limit (15 minutes) (ppm): 400

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

1-methoxy-2-propanol;monopropylene glycol methyl ether

| Duration: | Route of exposure: | DNEL: |
|---|--------------------|-------------------------|
| Long term – Systemic effects - General population | Dermal | 78 mg/kg bw/day |
| Long term – Systemic effects - Workers | Dermal | 183 mg/kg bw/day |
| Long term – Systemic effects - General population | Inhalation | 43.9 mg/m ³ |
| Long term – Systemic effects - Workers | Inhalation | 369 mg/m³ |
| Short term – Local effects - Workers | Inhalation | 553.5 mg/m ³ |
| Short term – Systemic effects - Workers | Inhalation | 553.5 mg/m ³ |
| Long term – Systemic effects - General population | Oral | 33 mg/kg bw/day |
| | | |

ethanol;ethyl alcohol

| Duration: | Route of exposure: | DNEL: |
|---|--------------------|------------------|
| Long term – Systemic effects - General population | Dermal | 206 mg/kg bw/day |
| Long term – Systemic effects - Workers | Dermal | 343 mg/kg bw/day |
| Long term – Systemic effects - General population | Inhalation | 114 mg/m³ |
| Long term – Systemic effects - Workers | Inhalation | 380 mg/m³ |
| Short term – Local effects - General population | Inhalation | 950 mg/m³ |
| Short term – Local effects - Workers | Inhalation | 1900 mg/m³ |
| Long term – Systemic effects - General population | Oral | 87 mg/kg bw/day |
| | | |

ethyl acetate



| Long term – Systemic effects - Workers Dermal 63 mg/kg bw/s Long term – Local effects - General population Inhalation 734 mg/m³ Long term – Systemic effects - General population Inhalation 367 mg/m³ Long term – Systemic effects - General population Inhalation 734 mg/m³ Short term – Local effects - General population Inhalation 734 mg/m³ Short term – Local effects - General population Inhalation 734 mg/m³ Short term – Systemic effects - Workers Inhalation 734 mg/m³ Short term – Systemic effects - General population Inhalation 734 mg/m³ Short term – Systemic effects - General population Inhalation 734 mg/m³ Inhalation 734 mg/m³ Inhalation 734 mg/m³ | | | |
|--|--|--------------------|-----------------------|
| Long term – Systemic effects - Workers Long term – Local effects - General population Long term – Local effects - Workers Inhalation Track to the systemic effects - Workers Long term – Systemic effects - General population Long term – Systemic effects - Workers Inhalation Track to the sys | Duration: | Route of exposure: | DNEL: |
| Long term – Local effects - General population Long term – Local effects - Workers Inhalation 734 mg/m³ Long term – Systemic effects - General population Long term – Systemic effects - Workers Inhalation 734 mg/m³ Short term – Local effects - General population Inhalation 734 mg/m³ Short term – Local effects - General population Inhalation 734 mg/m³ Short term – Local effects - Workers Inhalation 1468 mg/m³ Short term – Systemic effects - General population Inhalation 734 mg/m³ Short term – Systemic effects - General population Inhalation 734 mg/m³ Inhalation 734 mg/m³ | Long term – Systemic effects - General population | Dermal | 37 mg/kg bw/day |
| Long term – Local effects - Workers Inhalation 734 mg/m³ Long term – Systemic effects - General population Long term – Systemic effects - Workers Inhalation 734 mg/m³ Short term – Local effects - General population Inhalation 734 mg/m³ Short term – Local effects - Workers Inhalation 734 mg/m³ Short term – Local effects - Workers Inhalation 734 mg/m³ Short term – Systemic effects - General population Inhalation 734 mg/m³ Short term – Systemic effects - General population Inhalation 734 mg/m³ Inhalation 734 mg/m³ | Long term – Systemic effects - Workers | Dermal | 63 mg/kg bw/day |
| Long term – Systemic effects - General population Inhalation 367 mg/m³ Long term – Systemic effects - Workers Inhalation 734 mg/m³ Short term – Local effects - General population Inhalation 734 mg/m³ Short term – Local effects - Workers Inhalation 1468 mg/m³ Short term – Systemic effects - General population Inhalation 734 mg/m³ Short term – Systemic effects - Workers Inhalation 1468 mg/m³ | Long term – Local effects - General population | Inhalation | 367 mg/m ³ |
| Long term - Systemic effects - WorkersInhalation734 mg/m³Short term - Local effects - General populationInhalation734 mg/m³Short term - Local effects - WorkersInhalation1468 mg/m³Short term - Systemic effects - General populationInhalation734 mg/m³Short term - Systemic effects - WorkersInhalation1468 mg/m³ | Long term – Local effects - Workers | Inhalation | 734 mg/m³ |
| Short term – Local effects - General population Inhalation 734 mg/m³ Short term – Local effects - Workers Inhalation 1468 mg/m³ Short term – Systemic effects - General population Inhalation 734 mg/m³ Short term – Systemic effects - Workers Inhalation 1468 mg/m³ | Long term – Systemic effects - General population | Inhalation | 367 mg/m³ |
| Short term - Local effects - WorkersInhalation1468 mg/m³Short term - Systemic effects - General populationInhalation734 mg/m³Short term - Systemic effects - WorkersInhalation1468 mg/m³ | Long term – Systemic effects - Workers | Inhalation | 734 mg/m³ |
| Short term – Systemic effects - General population Inhalation 734 mg/m³ Short term – Systemic effects - Workers Inhalation 1468 mg/m³ | Short term – Local effects - General population | Inhalation | 734 mg/m³ |
| Short term – Systemic effects - Workers Inhalation 1468 mg/m³ | Short term – Local effects - Workers | Inhalation | 1468 mg/m³ |
| | Short term – Systemic effects - General population | Inhalation | 734 mg/m³ |
| Long term. Systemic effects. Coperal population. Oral. 4.5 mg/kg byy | Short term – Systemic effects - Workers | Inhalation | 1468 mg/m³ |
| Long term – Systemic effects - General population Oral 4.5 mg/kg bw/ | Long term – Systemic effects - General population | Oral | 4.5 mg/kg bw/day |

PNEC

1-methoxy-2-propanol;monopropylene glycol methyl ether

| Route of exposure: | Duration of Exposure: | PNEC: |
|-----------------------------------|-----------------------|------------|
| Freshwater | | 10 mg/L |
| Freshwater sediment | | 52.3 mg/kg |
| Intermittent release (freshwater) | | 100 mg/L |
| Marine water | | 1 mg/L |
| Marine water sediment | | 5.2 mg/kg |
| Sewage treatment plant | | 100 mg/L |
| Soil | | 4.59 mg/kg |

ethyl acetate

| ethyr acetate | | |
|-----------------------------------|-----------------------|------------|
| Route of exposure: | Duration of Exposure: | PNEC: |
| Freshwater | | 240 μg/L |
| Freshwater sediment | | 1.15 mg/kg |
| Intermittent release (freshwater) | | 1.65 mg/L |
| Marine water | | 24 μg/L |
| Marine water sediment | | 115 μg/kg |
| Predators | | 200 mg/kg |
| Sewage treatment plant | | 650 mg/L |
| Soil | | 148 µg/kg |

8.2. Exposure controls

Apply general control to prevent unnecessary exposure

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures



In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

| Туре | Class | Colour | Standards | |
|-----------------------------------|-------------|-----------------------------------|-----------|--|
| Combination filter A1B2E1K1-P3 | Class 1/2/3 | Brown/Gray/Yellow/Greer /White | n EN14387 | |

Skin protection

| Recommended | Type/Category | Standards | |
|---|---------------|-----------|---|
| Dedicated work clothing should be worn. | - | - | R |



Hand protection

| Material | Glove thickness (mm) | Breakthrough time (min.) | Standards | |
|----------|----------------------|-----------------------------|-----------|--|
| Nitrile | - | - | EN374-2 | |



Eye protection

| Туре | Standards |
|----------------|-----------|
| Safety glasses | EN166 |



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Clear

Odour / Odour threshold

Testing not relevant or not possible due to the nature of the product.

рΗ

Density (g/cm³)

Approx. 0.82

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Refresh



Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

78

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

13

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

No data available

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to the nature of the product.

n-octanol/water coefficient (LogKow)

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Evaporation rate (n-butylacetate = 100)

~200

VOC (g/l)

950

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

Extremes of temperature

Sunlight

10.5. Incompatible materials

Strong acids

Strong oxidizing agents



10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure. Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil



No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

Not applicable.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

| | 14.1 14.2 UN / ID UN proper shipping name | 14.3 Hazard class(es) | 14.4 PG* | 14.5 Env** | Other information: |
|------|--|--|-------------|---------------|--|
| ADR | UN1993 FLAMMABLE LIQUID, N.O.S. | Transport hazard class: 3 Label: 3 Classification code: F1 | III | No | Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information. |
| IMDG | - | - | - | - | - |
| IATA | | - | - | - | - |
| | | | | | |

^{*} Packing group

Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: ●3Y

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

^{**} Environmental hazards



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

UK-REACH, Annex XVII

ethanol; ethyl alcohol is subject to UK-REACH restrictions (entry 40).

1-methoxy-2-propanol;monopropylene glycol methyl ether is subject to UK-REACH restrictions (entry 40). ethyl acetate is subject to UK-REACH restrictions (entry 40).

Additional information

Tactile warning.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue



GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Spencer Thomas

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en